

CLAIMS

I claim:

1. A fluid machine comprising:
- a housing defining an interior, the housing having a port in communication with the interior of the housing;
- at least one primary vane disposed within the interior of the housing that rotates about a primary axis;
- at least one secondary vane disposed within the interior of the housing, the secondary vane pivotally oscillating between alternating open and closed positions with respect to the primary vane and defining a chamber within the housing interior having a volume which varies as the primary vane is rotated about the primary axis; and
- an actuator for varying the point during rotation of the primary vane at which the secondary vane reaches the open and closed positions relative to the port so that communication of the port with the chamber is adjusted.
2. The fluid machine of claim 1, wherein the actuator varies the point during rotation of the primary vane at which the secondary vane reaches the open and closed positions so that the rate of fluid flow through the machine is varied.
3. The fluid machine of claim 1, wherein the actuator varies the point during rotation of the primary vane at which the secondary vane reaches the open and closed positions so that the direction of fluid flow through the machine is reversed while the direction of rotation of the primary vane remains substantially constant.

1 4. The fluid machine of claim 1, wherein:
2 the actuator includes a control member that is adjusted
3 relative to the housing to varying the point during rotation
4 of the primary vane at which the secondary vane reaches the
5 open and closed positions so that the degree of
6 communication of the port with the chamber is adjusted.

1 5. The fluid machine of claim 4, wherein:
2 the control member is a control plate which couples to
3 the housing.

1 6. The fluid machine of claim 4, wherein:
2 the control member is a control lever.

1 7. The fluid machine of claim 1, wherein there are two
2 ports formed in the housing.

1 8. The fluid machine of claim 1, wherein at least a
2 substantial portion of the secondary vane is hollow.

1 9. The fluid machine of claim 1, wherein the secondary
2 vane is formed as two halves that are joined together, and
3 wherein at least one of the secondary vane halves has
4 recessed areas formed therein.

1 10. The fluid machine of claim 1, wherein the exterior of
2 the housing is contoured to provide increased surface area
3 to facilitate cooling of the machine.

1 11. The fluid machine of claim 1, wherein the exterior of
2 the housing is provided with a plurality of outwardly
3 projecting ribs.

1 12. The fluid machine of claim 1, wherein the fluid machine
2 is a motor.

1 13. The fluid machine of claim 1, wherein the fluid machine
2 is a fluid pump.

1 14. The fluid machine of claim 1, wherein the fluid machine
2 is a fluid compressor.

1 15. The fluid machine of claim 1, wherein the actuator
2 varies the point during rotation of the primary vane at
3 which the secondary vane reaches the open and closed
4 positions so that the rate of fluid flow through the machine
5 is adjusted while the direction of rotation of the primary
6 vane remains substantially constant.

1 16. The fluid machine of claim 1, wherein:
2 the actuator is adjustable to vary the lower limit of
3 the size of the volume of the chamber defined by the primary
4 and secondary vane that is in communication with the port.

RECEIVED "22670850

1 17. A fluid machine comprising:
2 a housing defining an interior, the housing having a
3 port in communication with the interior of the housing;
4 at least one primary vane disposed within the interior
5 of the housing that rotates about a primary axis;
6 at least one secondary vane disposed within the
7 interior of the housing, the secondary vane pivotally
8 oscillating between alternating open and closed positions
9 with respect to the primary vane and defining a chamber
10 within the housing interior having a volume which varies as
11 the primary vane is rotated about the primary axis; and
12 an actuator that is adjustable to vary the lower limit
13 of the size of the volume of the chamber defined by the
14 primary and secondary vane that is in communication with the
15 port.

09801972 030801

1 18. A fluid machine comprising:

2 a housing defining an interior, the housing having at
3 least two fluid ports in communication with the interior of
4 the housing;

5 a primary vane disposed within the interior of the
6 housing;

7 a rotary shaft having a primary axis that couples to
8 the primary vane and rotates the primary vane about the
9 primary axis;

10 a secondary vane mounted within the housing for pivotal
11 movement between open and closed positions with respect to
12 the primary vane, the secondary vane pivoting about a
13 pivotal axis passing through the primary vane as the primary
14 vane rotates, the primary and secondary vanes dividing the
15 interior of the housing into chambers with the volume of the
16 chambers varying as the secondary vane is moved between the
17 open and closed positions; and

18 a guide that causes the secondary vane to move between
19 the open and closed positions and directs diametrically
20 opposed points of the secondary vane to rotate about a
21 secondary vane rotational axis that intersects but which is
22 angularly offset from the primary axis as the primary vane
23 is rotated, the primary axis and secondary vane rotational
24 axis defining a control plane; and

25 wherein the guide can be adjusted to orient the control
26 plane in two or more positions so that communication of the
27 ports with the chambers is adjusted to thereby regulate
28 fluid flow through the machine.

1 19. The fluid machine of claim 18, wherein the rate of
2 fluid flow through the machine is varied by adjusting the
3 orientation of the control plane.

1 20. The fluid machine of claim 18, wherein the direction of
2 fluid flow through the machine is reversed by adjusting the
3 orientation of the control plane while the direction of
4 rotation of the primary vane remains substantially constant.

1 21. The fluid machine of claim 1, wherein the rate of fluid
2 flow through the machine is adjusted by adjusting the
3 orientation of the control plane while the direction of
4 rotation of the primary vane remains substantially constant.

09801972-030801

1 22. A fluid machine comprising:

2 a housing defining a generally spherical interior, the
3 housing having a fluid inlet and a fluid outlet in
4 communication with the interior of the housing;

5 a primary vane disposed within the interior of the
6 housing;

7 a rotary shaft having a primary axis of rotation
8 mounted to the housing, the primary vane being coupled to
9 the rotary shaft so that the primary vane is rotated about
10 the primary axis by the rotary shaft;

11 a fixed shaft which extends into the interior of the
12 housing opposite the rotary shaft, the fixed shaft having a
13 spherical end portion about which the primary vane rotates,
14 the fixed shaft being adjustably mounted to the housing so
15 that the fixed shaft can be oriented in various fixed
16 positions;

17 a carrier ring rotatably carried on the spherical end
18 portion of the fixed shaft, the axis of rotation of the
19 carrier ring being oriented at an oblique angle in relation
20 to the primary axis;

21 a secondary vane pivotally mounted to the rotary shaft
22 so that the secondary vane is pivotal about an axis
23 perpendicular to the primary axis to allow the secondary
24 vane to pivot between open and closed positions with respect
25 to the primary vane as the primary and secondary vanes are
26 rotated together by the rotary shaft about the primary axis,
27 the primary and secondary vanes dividing the interior of the
28 housing into chambers with the volume of the chambers
29 varying as the secondary vane is moved between the open and
30 closed positions, the secondary vane being pivotally coupled
31 to the carrier ring so that the secondary vane is pivotal
32 about an axis perpendicular to the carrier ring's axis of

09801972-030801

33 rotation, the rotation of the carrier ring causing the
34 secondary vane to reciprocate between the open and closed
35 positions as the secondary vane is rotated about the primary
36 axis by the rotary shaft; and wherein

37 the degree of communication of the inlet and outlet
38 ports with the chambers is adjusted by moving the fixed
39 shaft to a different fixed position.

1 23. The fluid machine of claim 22, wherein the rate of
2 fluid flow through the machine is adjusted by varying the
3 position of the fixed shaft.

1 24. The fluid machine of claim 22, wherein the direction of
2 fluid flow through the machine is reversed by varying the
3 position of the fixed shaft while the direction of rotation
4 of the rotary shaft remains substantially constant.

1 25. The fluid machine of claim 22, wherein:

2 the fixed shaft is rotatably mounted to the housing;
3 and further comprising:

4 a control lever coupled to the fixed shaft for
5 selectively rotating the fixed shaft to the various fixed
6 positions.

1 26. The fluid machine of claim 22, further comprising a
2 control member that couples to the fixed shaft for
3 maintaining the fixed shaft at a selected fixed position.

1 27. The fluid machine of claim 22, wherein there are two
2 inlets and two outlets formed in the housing.

1 28. The fluid machine of claim 22, wherein at least a
2 substantial portion of the secondary vane is hollow.

1 29. The fluid machine of claim 22, wherein the secondary
2 vane is formed as two halves that are joined together, and
3 wherein at least one of the secondary vane halves has
4 recessed areas formed therein.

1 30. The fluid machine of claim 22, wherein the primary and
2 secondary vanes divide the interior of the housing into four
3 chambers.

1 31. The fluid machine of claim 22, wherein the secondary
2 vane is pivotally mounted to the rotary shaft by pivotally
3 coupling the secondary vane to the primary vane.

1 32. The fluid machine of claim 22, wherein the fixed shaft
2 is moved to the various fixed positions by rotating the
3 fixed shaft about an axis coaxial with the primary axis.

1 33. The fluid machine of claim 22, wherein the exterior of
2 the housing is contoured to provide increased surface area
3 to facilitate cooling of the machine.

1 34. The fluid machine of claim 22, wherein the exterior of
2 the housing is provided with a plurality of outwardly
3 projecting ribs.

1 35. The fluid machine of claim 22, wherein the fluid
2 machine is a motor.

1 36. The fluid machine of claim 22, wherein the fluid
2 machine is a fluid pump.

0980197-030860

1 37. The fluid machine of claim 22, wherein the fluid
2 machine is a fluid compressor.

1 38. The fluid machine of claim 22, wherein the rate of
2 fluid flow through the machine is adjusted by varying the
3 position of the fixed shaft, while the rotary shaft is
4 rotated at a generally constant rate.

1 39. A method of regulating fluid flow in a fluid machine
2 comprising:

3 providing a housing of the machine that defines a
4 housing interior, the housing having a port in communication
5 with the interior of the housing through which fluid from a
6 fluid source is allowed to flow;

7 providing at least one primary vane disposed within the
8 interior of the housing that rotates about a primary axis;

9 providing at least one secondary vane disposed within
10 the interior of the housing;

11 rotating the primary vane about the primary axis with
12 the secondary vane pivotally oscillating between alternating
13 open and closed positions with respect to the primary vane
14 defining a fluid chamber for containing fluid within the
15 housing interior having a volume that varies as the primary
16 vane is rotated about the primary axis; and

17 varying the point at which the secondary vane reaches
18 the open and closed positions relative to the port so that
19 the degree of communication of the port with the fluid
20 chamber defined by the primary and secondary vanes can be
21 adjusted to vary the fluid flow through the port.

1 40. The method of claim 39, wherein the direction of fluid
2 flow is reversed by varying the point at which the secondary
3 vane reaches the open and closed positions relative to the
4 port.

1 41. The method of claim 40, wherein the direction of
2 rotation of the primary vane about the primary axis remains
3 substantially constant.

1 42. The method of claim 39, wherein the rate of flow of the
2 fluid through the device is changed by varying the point at

09801972 09801

3 which the secondary vane reaches the open and closed
4 positions relative to the port.

1 43. The method of claim 42, wherein the rate of rotation of
2 the primary vane about the primary axis is maintained
3 substantially constant.

1 44. The method of claim 39, wherein the fluid is a
2 compressible fluid.

1 45. The method of claim 39, wherein the fluid is a non-
2 compressible fluid.

0380197-030801
"246T0860"

1 46. A method of regulating fluid flow in a fluid machine
2 comprising:

3 providing a housing of the machine having a hollow
4 interior and having at least two fluid ports in
5 communication with the housing interior, at least one of the
6 ports connected to a fluid source;

7 rotating a primary vane within the interior of the
8 housing about a primary axis;

9 providing a secondary vane that is mounted within the
10 housing for pivotal movement between open and closed
11 positions with respect to the primary vane, the secondary
12 vane pivoting about a pivotal axis passing through the
13 primary vane as the primary vane rotates, the primary and
14 secondary vanes dividing the interior of the housing into
15 chambers, with the volume of the chambers varying as the
16 secondary vane is moved between the open and closed
17 positions;

18 guiding the secondary vane to move between the open and
19 closed positions so that diametrically opposed points on the
20 secondary vane rotate about a secondary vane rotational axis
21 that intersects but which is angularly offset from the
22 primary axis as the primary vane is rotated, the primary
23 axis and secondary vane rotational axis defining a control
24 plane; and

25 adjusting the orientation of the control plane in two
26 or more positions so that communication of the ports with
27 the chambers is adjusted to thereby regulate fluid flow
28 through the machine.

1 47. The method of claim 46, wherein the direction of fluid
2 flow is reversed by adjusting the orientation of the control
3 plane.

1 48. The method of claim 47, wherein the direction of
2 rotation of the primary vane about the primary axis remains
3 constant.

1 49. The method of claim 46, wherein the rate of flow of the
2 fluid through the device is changed by adjusting the
3 orientation of the control plane.

1 50. The method of claim 49, wherein the rate of rotation of
2 the primary vane about the primary axis is maintained
3 substantially constant.

1 51. The method of claim 49, wherein the fluid is a
2 compressible fluid

1 52. The method of claim 46, wherein the fluid is a non-
2 compressible fluid.

09801972.030801
TUBED "246T0860"

1 53. A method of regulating fluid flow in a fluid machine
2 comprising:

3 providing a housing of the machine having a spherical
4 hollow interior and having first and second fluid ports that
5 are spaced apart from each other to provide fluid
6 communication between the exterior of the housing and the
7 interior, at least one of the first and second ports
8 connected to a fluid source;

9 providing a primary vane disposed within the housing,
10 the primary vane being rotatable about a primary axis;

11 providing a fixed shaft that extends into the housing
12 interior, the fixed shaft having a spherical end portion
13 disposed within the interior about which the primary vane
14 rotates, the fixed shaft being adjustably mounted to the
15 housing so that the fixed shaft can be oriented in various
16 fixed positions;

17 providing a carrier ring rotatably mounted on the
18 spherical end portion of the fixed shaft, the carrier ring
19 rotating about a carrier ring axis that is oriented at an
20 oblique angle with respect to the primary axis;

21 providing a secondary vane that is pivotally mounted to
22 the primary vane so that the secondary vane is pivotal about
23 an axis perpendicular to the primary axis to allow the
24 secondary vane to pivot between open and closed positions
25 with respect to the primary vane as the primary and secondary
26 vane are rotated together about the primary axis, the
27 primary and secondary vanes dividing the interior of the
28 housing into chambers, the secondary vane being pivotally
29 coupled to the carrier ring so that the secondary vane is
30 pivotal about an axis perpendicular to the carrier ring
31 axis;

0901972 030801

32 rotating the primary and secondary vane about the
33 primary axis while the fixed shaft is in a first fixed
34 position, the rotation of the secondary vane about the
35 primary axis causing the carrier ring to rotate about the
36 carrier ring axis and thus cause the secondary vane to
37 reciprocate between the open and closed positions as the
38 primary and secondary vane are rotated about the primary
39 axis, the primary and secondary vanes defining an inlet
40 chamber as the secondary vane is reciprocated to the open
41 position so that fluid enters the inlet chamber through the
42 first port while the first port is in communication with the
43 inlet chamber, and wherein the primary and secondary vanes
44 define a discharge chamber as the secondary vane is
45 reciprocated to the closed position so that fluid exits the
46 discharge chamber through the second port while the second
47 port is in communication with the discharge chamber; and

48 moving the fixed shaft to a second position so that the
49 degree of communication of the first and second ports with
50 the inlet and discharge chambers defined by the primary and
51 secondary vanes as the primary and secondary vanes are
52 rotated about the primary axis is changed to vary the fluid
53 flow through the machine.

1 54. The method of claim 53, wherein the direction of fluid
2 flow is reversed when the fixed shaft is moved to the second
3 position, the first port communicating with the discharge
4 chamber and the second port communicating with the inlet
5 chamber when the fixed shaft is in the second position.

1 55. The method of claim 54, wherein the direction of
2 rotation of the primary and secondary vanes about the
3 primary axis remains substantially constant.

1 56. The method of claim 53, wherein the rate of flow of the
2 fluid through the device is changed when the fixed shaft is
3 moved to the second position.

1 57. The method of claim 56, wherein the rate of rotation of
2 the primary and secondary vanes about the primary axis is
3 maintained substantially constant.

1 58. The method of claim 53, wherein a lever is provided
2 with the fixed shaft to facilitate rotating of the fixed
3 shaft to the second fixed positions.

1 59. The method of claim 53, wherein a control member is
2 provided with the fixed shaft, the control member mounting
3 to the housing and engaging the fixed shaft so that the
4 fixed shaft is maintained in the desired fixed position.

09801972-030801

1 60. A race assembly of a spherical fluid machine for
2 causing a reciprocating vane of the fluid machine to
3 oscillate back and forth while rotating about a primary axis
4 within a housing of the fluid machine, the race assembly
5 comprising:

6 a carrier ring shaft that mounts within the housing of
7 the fluid machine;

8 a carrier ring for coupling to the reciprocating vane,
9 the carrier ring rotatably mounting to the carrier ring
10 shaft so that the carrier ring rotates about a second axis
11 that is at an oblique angle with respect to the primary
12 axis;

13 a first shaft end portion that is joined to one end of
14 the carrier ring shaft; and

15 a second shaft end portion that mounts to the other end
16 of the carrier ring shaft and is secured thereto by at least
17 two removable fasteners that are eccentrically located with
18 respect to the second axis.

09801972 030801

1 61. A vane for a rotary vane fluid machine comprising:
2 a vane member wherein at least a substantial portion of
3 the vane member is hollow so that the weight of the vane is
4 reduced.

1 62. The vane of claim 61, wherein:
2 the vane is formed as two halves that are joined
3 together, and wherein at least one of the vane halves has a
4 recessed area formed therein.

1 63. A housing for a rotary vane fluid machine, comprising:
2 a housing body having an exterior surface that is
3 contoured to provide increased surface area for heat
4 transfer.

1 64. A housing for a rotary vane fluid machine, comprising:
2 a housing body having a plurality of outwardly
3 projecting ribs formed on the exterior of the housing body.

09801972-030801
T080E0"226T0860